# NSN 5930-00-621-8655

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-621-8655

| view Offinite at https://aerobasegroup.com/nsi//0330-00-021-0000            |  |
|---|--|
| Thread Class:   |  |
| 2b all threaded hole  |  |
| Overall Length:   |  |
| 3.469 inches  |  |
| Overall Height:   |  |
| 4.813 inches  |  |
| Overall Width:  |  |
| 2.000 inches  |  |
| Body Length:  |  |
| 3.469 inches  |  |
| Distance Between Mounting Facility Centers:                                 |  |
| 1.000 inches  |  |
| Capillary Tube Length:  |  |
| 76.000 inches   |  |
| Bulb Length:  |  |
| 1.500 inches  |  |
| Bulb Diameter:  |  |
| 0.375 inches  |  |
| Tempurature Sensing Element Type:   |  |
| Capillary tube-bulb   |  |
| Mounting Method:  |  |
| Threaded hole   |  |
| Features Provided:  |  |
| Electrical access port  |  |
| Thready Qty Per Inch (tpi):   |  |
| 32 all threaded hole  |  |
| Contact Action Stimulus:  |  |
| Increase  |  |
| Thread Size:  |  |
| 0.190 inches all threaded hole  |  |
| Mounting Facility Pattern:  |  |
| Two position in-line  |  |
| Nonpile-up Contact Arrangement:   |  |
| 1 pole, single throw, normally open, momentary action                       |  |
| Terminal Type:  |  |
| Screw   |  |
| Contact Load Current Rating:  |  |
| 20.0 amperes resistive load second voltage                                  |  |
| Contact Adjustability:  |  |
| Deactuation point adjustable, preset and actuation point adjustable, preset |  |
| Contact Adjustment Range:   |  |

+0.00/+55.00 actuation point degrees fahrenheit and +0.00/+45.00 deactuation point degrees fahrenheit

# NSN 5930-00-621-8655

Thermostatic Switch - Page 2 of 2



#### **Contact Adjustment Type:**

External deactuation point knob and external actuation point knob

## **Contact Stimulus Rating:**

39.00 actuation point degrees fahrenheit and 41.00 actuation point degrees fahrenheit and 5.00 differential point degrees fahrenheit and 20.00 differential point degrees fahrenheit

## **Contact Voltage Rating In Volts:**

240.0 ac at sea level first voltage

#### Frequency In Hertz:

60.0 first voltage and 400.0 first voltage

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Rectangular

**Thread Series Designator:** 

Unf all threaded hole

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0