

View Online at <https://aerobasegroup.com/nsn/5930-00-621-9952>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Body Diameter:**

Between 1.015 inches and 1.045 inches

**Bushing Length:**

Between 0.325 inches and 0.355 inches

**Body Length:**

Between 1.015 inches and 1.045 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 inch-ounces

**Switch Actuating Force:**

16.0 inch-ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Specification Data:**

81349-mil-s-8805/85 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0