

View Online at <https://aerobasegroup.com/nsn/5930-00-621-9981>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Body Diameter:**

Between 0.328 inches and 0.358 inches

**Bushing Length:**

Between 0.267 inches and 0.297 inches

**Actuator Diameter:**

Between 0.141 inches and 0.171 inches

**Actuator Height:**

Between 0.121 inches and 0.151 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, double break, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

**Special Features:**

Clear case

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0