

View Online at <https://aerobasegroup.com/nsn/5930-00-622-0355>

**Thread Class:**

2a single mounting facility

**Overall Length:**

2.958 inches

**Overall Height:**

2.219 inches

**Overall Width:**

2.063 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.249 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Nonturn Device Radius:**

0.490 inches at 12: 00 o'clock and 0.510 inches at 12: 00 o'clock

**Distance Between Mounting Facility Centers:**

1.375 inches single mounting facility

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

16 each section rear

**Mounting Method:**

Threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Shaft Flat/slot Angular Location:**

150.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

4.0 amperes resistive load dc at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0