NSN 5930-00-623-0213

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-623-0213

·
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.465 inches
Overall Height:
3.435 inches
Overall Width:
1.000 inches
Body Diameter:
1.000 inches
Bushing Length:
1.000 inches
Body Length:
2.060 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
1.375 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
64 0 ounces

Actuator Movement:

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

NSN 5930-00-623-0213

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0