NSN 5930-00-624-7393

Rotary Switch - Page 1 of 2



93

View Online at https://aerobasegroup.com/nsn/5930-00-624-73
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.781 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.000 inches single actuator
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
1.641 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.641 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

NSN 5930-00-624-7393

Rotary Switch - Page 2 of 2



Mounting Facility Pattern: Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 1 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Special Features:** Name plate included **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A052b0