NSN 5930-00-624-8375

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-624-8375

Overall Length:

Between 4.580 inches and 4.640 inches

Overall Height:

2.156 inches

Overall Width:

2.110 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.580 inches 2nd mounting facility and 1.600 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 1st section rear

Throw Quantity:

11 1st section rear

Mounting Method:

Bracket 2nd mounting facility and threaded stud 2nd mounting facility

Contact Voltage Rating In Volts:

28.0 lowest dc voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load highest dc voltage rating at sea level

Special Features:

Solenoid operated; one on front, one on rear

Style Designator:

Tap, square frame

Shelf Life:

N/a

NSN 5930-00-624-8375 Rotary Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A052b0