

View Online at <https://aerobasegroup.com/nsn/5930-00-626-4100>

**Overall Length:**

Between 0.730 inches and 0.770 inches

**Overall Height:**

1.312 inches

**Overall Width:**

Between 0.328 inches and 0.360 inches

**Body Length:**

Between 0.734 inches and 0.766 inches

**Body Width:**

Between 0.315 inches and 0.321 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.133 inches

**Distance Between Mounting Facility Centers:**

Between 0.455 inches and 0.465 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.5 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

110.00 actuation point degrees fahrenheit and 116.00 actuation point degrees fahrenheit and 105.00 deactuation point degrees fahrenheit and 111.00 deactuation point degrees fahrenheit and 5.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0