

View Online at <https://aerobasegroup.com/nsn/5930-00-626-4100>

Overall Length:

Between 0.730 inches and 0.770 inches

Overall Height:

1.312 inches

Overall Width:

Between 0.328 inches and 0.360 inches

Body Length:

Between 0.734 inches and 0.766 inches

Body Width:

Between 0.315 inches and 0.321 inches

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.133 inches

Distance Between Mounting Facility Centers:

Between 0.455 inches and 0.465 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.5 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

110.00 actuation point degrees fahrenheit and 116.00 actuation point degrees fahrenheit and 105.00 deactuation point degrees fahrenheit and 111.00 deactuation point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0