

View Online at <https://aerobasegroup.com/nsn/5930-00-626-4151>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.380 inches

**Body Width:**

0.390 inches

**Body Height:**

0.975 inches

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Actuator Length:**

0.370 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.687 inches

**Actuator Roller Diameter:**

0.211 inches

**Actuator Roller Width:**

0.156 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

12.0 ounces

**Switch Actuating Force:**

48.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.075 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0