

View Online at <https://aerobasegroup.com/nsn/5930-00-626-9736>

Thread Class:

2b 2nd mounting facility

Overall Height:

11.625 inches

Unthreaded Mounting Hole Diameter:

0.531 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

6.375 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Cam Actuated Switch Contact Arrangement:

6 pole, single throw, both positions maintained single switch each section in-line

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section in-line

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0