## NSN 5930-00-628-5030

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-628-5030
Thread Class:
2a single threaded bushing
Overall Length:
0.373 inches
Body Length:
0.170 inches
Tempurature Sensing Element Type:
Internal sensor
Width Across Flats:
0.281 inches
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 350.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
28 single threaded bushing
Contact Action Stimulus:
Decrease
Thread Size:
0.250 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
500.0 milliamperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
30.00 differential point degrees fahrenheit and 210.00 actuation point degrees fahrenheit and 240.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:

## **Test Data Document:**

Plug

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5930-00-628-5030

Thermostatic Switch - Page 2 of 2



Thread Series Designator:
Unf single threaded bushing
Specification Data:
81349-mil-s-24236/19 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A048b0

Demilitarization: