

View Online at <https://aerobasegroup.com/nsn/5930-00-628-7100>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

0.990 inches

Bushing Length:

0.440 inches

Actuator Length:

0.630 inches

Actuator Style:

Rectangular

Actuator Height:

0.640 inches

Actuator Width:

0.630 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

Test/lamp single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0