NSN 5930-00-628-7509

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-628-7509

Thread Class:

2b single mounting facility

Overall Length:

Between 2.564 inches and 2.688 inches

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.907 inches single actuator and 0.969 inches single actuator

Overall Diameter:

1.750 inches

Distance Between Mounting Facility Centers:

1.360 inches single mounting facility and 1.390 inches single mounting facility

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

3 single section front

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-628-7509

Rotary Switch - Page 2 of 2



| Contact Load | Current | Rating: |
|--------------|---------|---------|
|--------------|---------|---------|

2.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0