## NSN 5930-00-628-7509

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-628-7509

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

Between 2.564 inches and 2.688 inches

**Shaft Diameter:** 

0.249 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.907 inches single actuator and 0.969 inches single actuator

**Overall Diameter:** 

1.750 inches

**Distance Between Mounting Facility Centers:** 

1.360 inches single mounting facility and 1.390 inches single mounting facility

**Individual Section Quantity:** 

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section front

**Throw Quantity:** 

3 single section front

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Mounting Facility Pattern:** 

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round single actuator

Terminal Type:

Turret

**Contact Switching Action:** 

Breaks before makes single section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-628-7509

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

2.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0