NSN 5930-00-629-0279

Pressure-thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-629-0279

| Overall Length: |
|---|
| 7.250 inches |
| Overall Height: |
| 2.250 inches |
| Capillary Tube Length: |
| 72.0 inches |
| Pressure Switch Type: |
| Differential |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Threaded hole |
| Contact Action Stimulus: |
| |
| Decrease Proof Processes |
| Proof Pressure: |
| 220.00 degrees fahrenheit |
| Mounting Facility Pattern: |
| Isosceles triangle |
| Nonpile-up Contact Arrangement: |
| 2 pole, single throw, both positions maintained |
| Terminal Type: |
| Wire loop |
| Contact Load Current Rating: |
| 5.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| +100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External deactuation point pointer with scale and external actuation point pointer with scale |
| Contact Voltage Rating In Volts: |
| 240.0 ac at sea level first voltage |
| Pressure Connector Type: |
| External seat-gasket seal, threaded external single connection |
| Special Features: |
| Tilting type hermetically sealed mercury switch, 4 terminals |
| Media For Which Designed: |
| Gas or liquid |
| Thread Series Designator: |
| Nps single pressure connection |
| Shelf Life: |

N/a

NSN 5930-00-629-0279

Pressure-thermostatic Switch - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A048b0