

View Online at <https://aerobasegroup.com/nsn/5930-00-629-0282>

Overall Length:

7.250 inches

Overall Height:

3.375 inches

Body Diameter:

5.750 inches

Pressure Switch Type:

Differential

Width Across Flats:

0.563 inches

Mounting Method:

Threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+10.00/+200.00 actuation point pounds per square inch gage and +10.00/+200.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point knob with scale and internal deactuation point knob with scale

Contact Stimulus Rating:

4.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Special Features:

Steel bourdon tubes, motor 1 phase, 0.125 hp, magnetic sealed mercury contact

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0