

View Online at <https://aerobasegroup.com/nsn/5930-00-629-0293>

Overall Length:

4.190 inches

Overall Height:

4.130 inches

Overall Width:

3.500 inches

Mounting Slot Width:

0.280 inches

Body Length:

3.250 inches

Distance Between Mounting Facility Centers:

2.500 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Flange and slot

Features Provided:

Calibrated scale

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

180.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

3.0 amperes inductive load first voltage and 0.5 amperes inductive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.80/+100.00 actuation point pounds per square inch gage and +3.80/+100.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Stimulus Rating:

2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0