

View Online at <https://aerobasegroup.com/nsn/5930-00-629-0293>

**Overall Length:**

4.190 inches

**Overall Height:**

4.130 inches

**Overall Width:**

3.500 inches

**Mounting Slot Width:**

0.280 inches

**Body Length:**

3.250 inches

**Distance Between Mounting Facility Centers:**

2.500 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Mounting Method:**

Flange and slot

**Features Provided:**

Calibrated scale

**Thread Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

180.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

3.0 amperes inductive load first voltage and 0.5 amperes inductive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.80/+100.00 actuation point pounds per square inch gage and +3.80/+100.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point dial and external deactuation point dial

**Contact Stimulus Rating:**

2.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0