

View Online at <https://aerobasegroup.com/nsn/5930-00-629-6660>

Thread Class:

3b all pressure connection

Thread Length:

0.620 inches all threaded stud

Overall Length:

3.900 inches

Overall Diameter:

2.375 inches

Distance Between Mounting Facility Centers:

1.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Decrease

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

180.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

25.50 actuation point pounds per square inch and 24.00 deactuation point pounds per square inch and 1.50 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0