NSN 5930-00-629-8334

Sensitive Switch - Page 1 of 1

No Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-00-629-8334 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Oiltight **Housing Height:** 1.438 inches **Housing Length:** 3.875 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.062 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 3.062 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 600.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 two circuit, one position momentary single switch unit **Switch Actuating Force:** 44.000 inch-ounces **Actuator Movement:** 5.0 pretravel degrees and 25.0 overtravel degrees and 2.5 differential degrees **Contact Load Current Rating At Maximum Rated Voltage:** 20.000 milliamperes resistive dc and 20.000 milliamperes inductive dc and 15.000 amperes resistive ac and 5.000 amperes inductive ac **Precious Material And Location:** Contacts silver **Terminal Type And Quantity:** 4 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:**