

View Online at <https://aerobasegroup.com/nsn/5930-00-630-2176>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.687 inches

Bushing Length:

0.500 inches

Body Length:

1.800 inches

Body Width:

0.812 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Height:

0.904 inches

Actuator Free Position Height:

0.830 inches

Maximum Voltage Rating In Volts:

110.0 ac and 110.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded bushing

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

12.0 ounces

Actuator Movement:

Between 0.074 pretravel inches and 0.219 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0