

View Online at <https://aerobasegroup.com/nsn/5930-00-630-2176>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.687 inches

**Bushing Length:**

0.500 inches

**Body Length:**

1.800 inches

**Body Width:**

0.812 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.326 inches

**Actuator Height:**

0.904 inches

**Actuator Free Position Height:**

0.830 inches

**Maximum Voltage Rating In Volts:**

110.0 ac and 110.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, single throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

12.0 ounces

**Actuator Movement:**

Between 0.074 pretravel inches and 0.219 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 20.000 amperes resistive ac

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0