NSN 5930-00-630-6157

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-630-6157

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Industrial use
Overall Length:
2.062 inches
Overall Height:
5.825 inches
Overall Width:
3.250 inches
Actuator Length:
1.250 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Length:
4.560 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.430 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.812 inches
Maximum Voltage Rating In Volts:
240.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 two circuit, one position momentary single switch unit
Switch Release Force:
1.0 inch-ounces
Switch Actuating Force:
12.0 inch-ounces
Actuator Movement:
17.0 pretravel degrees and 70.0 overtravel degrees and 11.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac
Special Features:

Item lever operates in clockwise direction

NSN 5930-00-630-6157 Sensitive Switch - Page 2 of 2



rerminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

Fiig: A053a0