NSN 5930-00-630-6158

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Industrial use



View Online at https://aerobasegroup.com/nsn/5930-00-630-6158

Overall Length:			
2.062 inches			
Overall Height:			
5.825 inches			
Overall Width:			
3.250 inches			
Actuator Length:			
1.250 inches			
Actuator Style:			
Roller arm			
Actuator Roller Diameter:			
0.750 inches			
Actuator Roller Width:			
0.250 inches			
Housing Length:			
4.560 inches			
Housing Width:			
3.250 inches			
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:			
2.430 inches			
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:			
2.812 inches			
Maximum Voltage Rating In Volts:			
240.0 ac and 240.0 dc			
Inclosure Type:			
Fully enclosed			
Nonpile-up Contact Arrangement:			
3 two circuit, double break/double make, one position momentary single switch unit			
Switch Release Force:			
1.0 inch-ounces			
Switch Actuating Force:			
12.0 inch-ounces			
Actuator Movement:			
17.0 pretravel degrees and 70.0 overtravel degrees and 11.0 differential degrees			
Contact Load Current Rating At Maximum Rated Voltage:			
500.000 milliamperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac			
Special Features:			
Item lever operates in counter clockwise direction			

NSN 5930-00-630-6158

Sensitive Switch - Page 2 of 2



Terminal	Type And	Quantity:
12 screw		

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0