## NSN 5930-00-630-6160

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-630-6160

Body Style: Hole mounted  Hazardous Locations/environmental Protection: Industrial use  Overall Length: 3.250 inches  Overall Height: 4.953 inches  Overall Width: 2.062 inches  Actuator Length: 1.250 inches  Actuator Style:  Roller arm
Hazardous Locations/environmental Protection: Industrial use Overall Length: 3.250 inches Overall Height: 4.953 inches Overall Width: 2.062 inches Actuator Length: 1.250 inches Actuator Style:
Industrial use  Overall Length: 3.250 inches  Overall Height: 4.953 inches  Overall Width: 2.062 inches  Actuator Length: 1.250 inches  Actuator Style:
Overall Length: 3.250 inches Overall Height: 4.953 inches Overall Width: 2.062 inches Actuator Length: 1.250 inches Actuator Style:
3.250 inches  Overall Height: 4.953 inches  Overall Width: 2.062 inches  Actuator Length: 1.250 inches  Actuator Style:
Overall Height: 4.953 inches Overall Width: 2.062 inches Actuator Length: 1.250 inches Actuator Style:
4.953 inches  Overall Width: 2.062 inches  Actuator Length: 1.250 inches  Actuator Style:
Overall Width:  2.062 inches  Actuator Length:  1.250 inches  Actuator Style:
2.062 inches  Actuator Length: 1.250 inches  Actuator Style:
Actuator Length: 1.250 inches Actuator Style:
1.250 inches Actuator Style:
Actuator Style:
-
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Length:
4.560 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.430 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.812 inches
Maximum Voltage Rating In Volts:
240.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
3 two circuit, one position momentary single switch unit
Switch Release Force:
1.0 inch-ounces
Switch Actuating Force:
12.0 inch-ounces
Actuator Movement:

17.0 pretravel degrees and 70.0 overtravel degrees and 11.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac

**Special Features:** 

Unactuated position of lever horizontal to the left clockwise movement to actuate

## NSN 5930-00-630-6160

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
12 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0