NSN 5930-00-630-6163

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-630-6163

| Body Style: |
|--|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Shock proof and watertight |
| Overall Length: |
| 5.703 inches |
| Overall Width: |
| 2.430 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 1.500 inches |
| Actuator Style: |
| Roller arm |
| Actuator Height: |
| 0.500 inches |
| Actuator Roller Diameter: |
| 0.750 inches |
| Actuator Roller Width: |
| 0.250 inches |
| Housing Height: |
| 1.940 inches |
| Housing Length: |
| 4.560 inches |
| Housing Width: |
| 2.312 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 2.430 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 2.812 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 600.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 inch-ounces |
| Switch Actuating Force: |
| 40.0 inch-ounces |
| Actuator Movement: |

10.0 pretravel degrees and 70.0 overtravel degrees and 11.0 differential degrees

NSN 5930-00-630-6163

Sensitive Switch - Page 2 of 2



| Contact Load Current Rating At Maximum Rated Voltage | Contact | Load | Current | Rating A | At Maximum | Rated | Voltage |
|--|---------|------|---------|----------|------------|-------|---------|
|--|---------|------|---------|----------|------------|-------|---------|

0.400 amperes resistive dc and 6.000 amperes resistive ac and 1.200 amperes inductive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0