

View Online at <https://aerobasegroup.com/nsn/5930-00-630-6163>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

5.703 inches

Overall Width:

2.430 inches

Case Material:

Metal

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.500 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

1.940 inches

Housing Length:

4.560 inches

Housing Width:

2.312 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.430 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.812 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

40.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 70.0 overtravel degrees and 11.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

0.400 amperes resistive dc and 6.000 amperes resistive ac and 1.200 amperes inductive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0