

View Online at <https://aerobasegroup.com/nsn/5930-00-631-3039>

Outside Diameter:

1.687 inches single connection

Overall Width:

2.093 inches

Body Length:

4.750 inches

Body Height:

3.875 inches

Distance Between Mounting Facility Centers:

2.250 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

20.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes motor load fifth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point not adjustable

Contact Adjustment Range:

+0.10/+4.50 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw with scale

Contact Stimulus Rating:

0.06 actuation point pounds per square inch and 4.50 actuation point pounds per square inch

Contact Voltage Rating In Volts:

550.0 dc at sea level fifth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0