

View Online at <https://aerobasegroup.com/nsn/5930-00-631-3231>

**Inside Diameter:**

0.250 inches all connections

**Overall Length:**

6.500 inches

**Overall Height:**

7.750 inches

**Body Diameter:**

7.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 110.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.125 inches all pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+2.00/+6.00 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw with scale

**Contact Voltage Rating In Volts:**

480.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/bracket

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0