

View Online at <https://aerobasegroup.com/nsn/5930-00-631-3252>

**Overall Length:**

7.875 inches

**Overall Height:**

2.250 inches

**Body Diameter:**

5.750 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches

**Longest Horizontal Distance Between Mounting Centers:**

7.000 inches

**Shortest Horizontal Distance Between Mounting Centers:**

3.500 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

10.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+2.00/+60.00 actuation point pounds per square inch gage and +2.00/+60.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point pointer with scale and external deactuation point pointer with scale

**Contact Stimulus Rating:**

4.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

440.0 ac at sea level first voltage

**Pressure Connector Type:**

External seat-gasket seal, threaded external single connection

**Style Designator:**

Cylindrical w/port

**Thread Series Designator:**

Nps single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0