## NSN 5930-00-631-3737

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-631-3737 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Bushing Length:** 0.359 inches **Body Length:** 0.781 inches **Body Width:** 0.562 inches **Body Height:** 0.672 inches **Case Material:** Metal **Maximum Voltage Rating In Volts:** 125.0 ac and 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive ac and 10.000 amperes resistive ac and 7.500 amperes resistive dc and 5.000 amperes inductive dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Unable To Decode:** Unable to decode and unable to decode **Thread Series Designator:** Uns **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-00-631-3737

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0