## NSN 5930-00-632-7812

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-632-7812
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
13.032 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Individual Section Quantity:
22
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
Н
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 each section front
Throw Quantity:
2 each section front
Mounting Facility Circle Radius:
1.625 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator

**Terminal Type:** 

Tab w/screw

## NSN 5930-00-632-7812

Rotary Switch - Page 2 of 2



011	0	A - (!
Contact	Switching	Action:

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

7.5 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0