

View Online at <https://aerobasegroup.com/nsn/5930-00-633-4434>

Thread Class:

3a single pressure connection

Overall Length:

7.250 inches

Outside Diameter:

0.438 inches single connection

Overall Height:

2.500 inches

Overall Width:

6.375 inches

Body Length:

5.500 inches

Body Width:

4.375 inches

Longest Horizontal Distance Between Mounting Centers:

5.375 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -35.0 degrees fahrenheit and 95.0 degrees fahrenheit

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

7.5 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+15.00/+400.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

3.00 differential point pounds per square inch and 13.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Double threaded section boss fitting gasket with locknut sealing, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0