NSN 5930-00-636-0036

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-0036

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant

Overall Length:

1.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.875 inches

Overall Width:

0.406 inches

Body Length:

1.093 inches

Body Width:

0.406 inches

Body Height:

Louy noight

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.016 differential inches

NSN 5930-00-636-0036

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0