

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0036>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant and moisture resistant

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.406 inches

**Body Length:**

1.093 inches

**Body Width:**

0.406 inches

**Body Height:**

0.625 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.110 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0