

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0226>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.365 inches and 1.385 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.870 inches and 0.880 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

0.406 inches

Body Height:

Between 0.615 inches and 0.635 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.401 inches and 0.411 inches

Actuator Style:

Round

Actuator Height:

Between 0.014 inches and 0.034 inches

Actuator Free Position Height:

0.859 inches

Actuator Roller Diameter:

0.859 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 28.5 dc

End Application:

Aircraft, b-52, c-135, t-37

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0