

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0226>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 1.365 inches and 1.385 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.870 inches and 0.880 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

0.406 inches

**Body Height:**

Between 0.615 inches and 0.635 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.401 inches and 0.411 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.014 inches and 0.034 inches

**Actuator Free Position Height:**

0.859 inches

**Actuator Roller Diameter:**

0.859 inches

**Actuator Adapter Style:**

Roller leaf

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.5 dc

**End Application:**

Aircraft, b-52, c-135, t-37

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0