NSN 5930-00-636-0232

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-0232 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Watertight **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.812 inches **Body Length:** 1.094 inches **Body Width:** 0.625 inches **Body Height:** 0.406 inches **Switch Actuator Quantity: Actuator Free Position Height:** 0.391 inches **Maximum Voltage Rating In Volts:** 125.0 ac **Inclosure Type:** Fully enclosed Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Actuator Movement:** Between 0.188 pretravel inches and 0.062 overtravel inches and 0.250 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive ac **Special Features:** Can be mounted on side of bracket **Thread Series Designator:** Unc **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-636-0232

Sensitive Switch - Page 2 of 2



Fiig:

A053a0