

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0238>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.906 inches

Overall Height:

1.500 inches

Overall Width:

0.906 inches

Bushing Length:

0.375 inches

Body Length:

0.624 inches

Body Width:

0.906 inches

Body Height:

0.906 inches

Case Material:

Metal

Actuator Length:

0.312 inches

Actuator Style:

Rectangular

Actuator Height:

0.188 inches

Actuator Width:

0.562 inches

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

15.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.070 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0