

NSN 5930-00-636-0238 Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-636-0238 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.906 inches **Overall Height:** 1.500 inches **Overall Width:** 0.906 inches **Bushing Length:** 0.375 inches **Body Length:** 0.624 inches **Body Width:** 0.906 inches **Body Height:** 0.906 inches **Case Material:** Metal **Actuator Length:** 0.312 inches **Actuator Style:** Rectangular **Actuator Height:**

0.188 inches

Actuator Width:

0.562 inches

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

NSN 5930-00-636-0238 Sensitive Switch - Page 2 of 2



Switch Release Force:
4.0 ounces
Switch Actuating Force:
15.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.070 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 6.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0