NSN 5930-00-636-0242

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Dustproof

Overall Length: 1.938 inches



View Online at https://aerobasegroup.com/nsn/5930-00-636-0242

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches	
Overall Height:	
1.375 inches	
Overall Width:	
0.688 inches	
Body Length:	
1.938 inches	
Body Width:	
0.688 inches	
Body Height:	
1.047 inches	
Unthreaded Mounting Hole Diameter:	
0.140 inches	
Actuator Style:	
Roller plunger	
Actuator Free Position Height:	
1.125 inches	
Actuator Roller Diameter:	
0.375 inches	
Actuator Roller Width:	
0.156 inches	
Maximum Voltage Rating In Volts:	
450.0 ac and 250.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary single switch unit	
Switch Release Force:	
3.0 ounces	
Switch Actuating Force:	
10.0 ounces	
Actuator Movement:	
Between 0.062 pretravel inches and 0.094 overtravel inches and 0.0	80

differential inches

NSN 5930-00-636-0242

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Special Features:

One mtg slot 0.152 in. By 0.140 in.

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0