NSN 5930-00-636-0243

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:

Blue color top



View Online at https://aerobasegroup.com/nsn/5930-00-636-0243

1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Overall Height:
1.375 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.828 inches
Unthreaded Mounting Hole Diameter:
Between 0.137 inches and 0.141 inches
Actuator Style:
Round
Actuator Diameter:
0.203 inches
Actuator Free Position Height:
1.115 inches
1.115 inches Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 600.0 ac
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 3.0 ounces
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 3.0 ounces Switch Actuating Force:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 3.0 ounces Switch Actuating Force: 14.0 ounces
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 3.0 ounces Switch Actuating Force: 14.0 ounces Actuator Movement:
Maximum Voltage Rating In Volts: 600.0 ac Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 3.0 ounces Switch Actuating Force: 14.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.062 overtravel inches and 0.001 differential inches

NSN 5930-00-636-0243

Sensitive Switch - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0