

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0472>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Submersible

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.796 inches and 1.828 inches

Body Length:

1.453 inches

Body Width:

Between 0.703 inches and 0.735 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.234 inches and 0.266 inches

Actuator Height:

Between 0.859 inches and 0.891 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0