

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0472>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Submersible

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.796 inches and 1.828 inches

**Body Length:**

1.453 inches

**Body Width:**

Between 0.703 inches and 0.735 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.234 inches and 0.266 inches

**Actuator Height:**

Between 0.859 inches and 0.891 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0