

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0574>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Waterproof

**Actuator Style:**

Round

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

Between 0.345 inches and 0.355 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes inductive dc and 1.000 amperes lamp dc and 10.000 amperes resistive dc

**Test Data Document:**

81349-mil-s-8805/37 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0