NSN 5930-00-636-0595

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-0595

Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Watertight						
Overall Length:						
8.031 inches						
Overall Height:						
3.062 inches						
Overall Width:						
3.250 inches						
Actuator Style:						
Roller plunger						
Actuator Free Position Height:						
1.906 inches						
Actuator Roller Diameter:						
1.000 inches						
Actuator Roller Width:						
0.250 inches						
Housing Height:						
3.062 inches						
Housing Length:						
6.125 inches						
Housing Width:						
3.250 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:						
5.250 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:						
2.375 inches						
Maximum Voltage Rating In Volts:						
440.0 ac and 250.0 dc						
Inclosure Type:						
Fully enclosed						
Nonpile-up Contact Arrangement:						
1 two circuit, one position momentary single switch unit						
Switch Actuating Force:						
368.0 ounces						
Actuator Movement:						
Between 0.310 pretravel inches and 0.158 overtravel inches and 0.035 differential inches						
Contact Load Current Rating At Maximum Rated Voltage:						

4 screw

Terminal Type And Quantity:

0.500 amperes resistive dc and 1.500 amperes resistive ac

NSN 5930-00-636-0595

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0