

View Online at <https://aerobasegroup.com/nsn/5930-00-636-0623>

First Flat Length:

0.625 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches single mounting facility

Individual Section Quantity:

18

Longest Horizontal Distance Between Mounting Centers:

3.812 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Base single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load lowest ac voltage rating at sea level

Special Features:

Auxiliary mounting method flush mtg four 1/4-20 thd mtg holes on 3.219in. Bolt circle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0