NSN 5930-00-636-0766

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-0766

Overall Length:					
6.188 inches					
Overall Height:					
2.125 inches					
Overall Width:					
2.125 inches					
First Flat Length:					
0.438 inches single actuator					
Flat Height:					
0.219 inches single actuator					
Shaft Diameter:					
0.250 inches single actuator					
Shaft Length:					
1.750 inches single actuator					
Individual Section Quantity:					
4					
Longest Horizontal Distance Between Mounting Centers:					
1.625 inches single mounting facility					
Longest Vertical Distance Between Mounting Centers:					
1.625 inches single mounting facility					
Switch Contact Basic Design:					
Nonpile-up symmetrical					
Nonpile-up symmetrical					
Nonpile-up symmetrical Thready Qty Per Inch (tpi):					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab w/screw					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab w/screw Contact Switching Action:					
Nonpile-up symmetrical Thready Qty Per Inch (tpi): 24 single mounting facility Thread Size: 0.190 inches single mounting facility Contact Voltage Rating In Volts: 120.0 ac at sea level Mounting Facility Pattern: Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front					

Contact Load Current Rating.

10.0 amperes resistive load ac at sea level

NSN 5930-00-636-0766

Rotary Switch - Page 2 of 2



Ī	hread	Series	Desig	nator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0