## NSN 5930-00-636-1278

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-1278

Thread	Length:
--------	---------

0.469 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

3.781 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.156 inches single actuator

**Shaft Diameter:** 

0.188 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Overall Diameter:** 

1.719 inches

**Individual Section Quantity:** 

3

**Knob Manufacturer Code:** 

81352

**Knob Manufacturer Part Number:** 

An3220

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section rear

**Throw Quantity:** 

7 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round, flatted single actuator

## NSN 5930-00-636-1278

Rotary Switch - Page 2 of 2



_								
	∩ni	201	. Sv	vitc	hın	$\alpha$	\ctic	۱n:

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Uns single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0